



1 1/2" x 1 1/2" Hose Rack Assembly



UL/ULC Listed and FM Approved red swing rack assembly. The hose rack assembly is a Class II Service and is an immediate and readily available means of controlling and suppressing fire by one person.

The semi-automatic swing rack with 25 moveable pins feature an automatic release mechanism, keeping water out of the hose (when valve is open) until the last fold is released.

Model M2507

- 1 1/2 Rack Red
- 1 1/2 Brass Angle Valve FxF with hydrolator
- 1 1/2 x 75 ft Rack Hose
- 1 1/2 Brass Adapter Nipple
- 1 1/2 Brass Fog Nozzles

Model M2510

- 1 1/2 Rack Red
- 1 1/2 Brass Angle Valve FxF with hydrolator
- 1 1/2 x 100 ft Rack Hose
- 1 1/2 Brass Adapter Nipple
- 1 1/2 Brass Fog Nozzles



www.amerex-mexico.com

ventas@amerex-mexico.com

Conmutador: (81) 1534.9214



Components:



UL/ULC Listed and FM Approved short, red swing rack that holds 1.5" (38 mm) x 75' and 100' rack hose. The hose rack is a Class II & Class III Service and is an immediate and readily available means of controlling and suppressing fire by one person.

300 lb (2070 KPa) pressure tested approved valve. Heavy Duty 1-1/2" (38 mm) angle hose and hydrolator valve. Automatically drains and vents, safeguarding against hose deterioration. O-ring packing and red cast handle. Forgeline Bonnett and Seat Assembly. UL/ULC listed and FM Approved.



Male to Male Hose rack nipple used with swinging hose rack. Same size both ends.

1.5" (38mm) Brass combination fog nozzle with bumper. UL / ULC Listed and FM Approved and adjusts from straight stream to fog to shutoff. Rated for up to 150 psi and used in most industrial applications, including hose rack and reel assemblies.



Interior Rack Hose designed for racks and reels for interior protection and occupant use applications. UL / ULC Listed and FM Approved.

Service Pressure: 250 PSI (1724 Kpa)
Proof Pressure: 500 PSI (3448 Kpa)



www.amerex-mexico.com

ventas@amerex-mexico.com

Conmutador: (81) 1534.9214

